



## China 608rs Bearing Supplier



6013 SKF, NSK, NTN, Koyo, Timken NACHI  
Tapered Roller Bearing, Spherical Roller Bearing,  
Pillow Block, Deep Groove Ball Bearing

Bearing No. 6013

6013 Bearing 2D drawings and 3D CAD models

Size	65x100x18 mm
Bore Diameter	65 mm
Outer Diameter	100 mm
Width	18 mm
d	65 mm
D	100 mm
B	18 mm
C	18 mm
r min.	1.1 mm
da min.	71 mm
Da max.	94 mm
ra max.	1.0 mm
Weight	0.438 Kg
Basic dynamic load rating (C)	30,5 kN
Basic static load rating (C0)	25,2 kN
(Grease) Lubrication Speed	6500 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NACHI
Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1   ISO P0



## China 608rs Bearing Supplier

Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	65MM Bore; 100MM Outside Diameter; 18MM Outer Race Width; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Other Features	Deep Groove
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.nachiamerica.com">http://www.nachiamerica.com</a>
Weight / LBS	1.0048
Bore	2.559 Inch   65 Millimeter
Outer Race Width	0.709 Inch   18 Millimeter
Outside Diameter	3.937 Inch   100 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Bore Type	Cylindrical Bore
Configuration	Single Row
Bore Size	65 mm
Width	18 mm
Fillet Radius/Chamfer	1.1 mm



## China 608rs Bearing Supplier

Dynamic Load Rating	30,500 N
Static Load Rating	25,200 N
Limiting Speed - Grease	6,700 rpm
Limiting Speed - Oil	8,000 rpm
Factor fo	15.7
Radial Clearance	0.008 to 0.028 mm
da (min)	71 mm
Da (max)	94 mm
ra (max)	1 mm